

TRADE GLAZE COAT



PRODUCT USES

Suitable for use over textured coatings such as DULUX TRADE SMOOTH RIPPLE.

Can also be used as a protective coating over matt finishes, to prevent marring.

Also recommended as a clear finish for brick and stone walls.

Dulux Trade Glazecoat is a clear, glaze coat for interior and exterior use



FEATURES AND BENEFITS

Clear and colourless, therefore the underlying colour of the substrate remains unaffected.

Acrylic gives excellent adhesion, ensuring long lasting protection for paint system.

Dries to a hard, glossy, non-yellowing finish which is easy to keep clean.

Totally compatible with other DULUX TRADE water-based coatings.

Good interior washability.



PRODUCT INFORMATION

Appearance	Gloss, but it will vary with film build and thinning ratio
Colour	Clear only. When viewed in the container, the material appears milky-white, but resultant film is clear
Density at 23°C	Approx. : 1.04 kg/L
Solids Content	By weight : Approx. 30%
Packaged Viscosity	Viscosity at 23°C : Approx 70 KU
Spreading Rate	Approx 12 m ² per litre depending on surface porosity, profile and application method
Recommended DFT per coat	Min. 25µm. Max. 35µm.



APPLICATION INFORMATION

Application conditions	Surface Temperature between 10°C - 35°C Relative Humidity between 10 % - 85 %
Application methods	Ready for use with brush or roller. A short-nap mohair roller is preferred. Heavy pile and foam rollers can create aeration problems
Thinner Water	Up to 2 litres water per 5 litre of DULUX TRADE GLAZE COAT may be added to reduce the gloss level
Drying Time	Touch dry 30 minutes (Drying times will be extended during cold, wet or humid conditions)
Recoating Time	4 hours
Cleaning of equipment	Clean immediately with water
Substrates	Suitable for application to brick and stone walls, walls painted with textured coatings, and wallpapered walls





APPLICATION INFORMATION

Precautions

Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry – no more than 12% moisture content.

Do not apply during cold (below 10°C) or wet weather.

Not suitable as a coating for floors.

Do not apply directly to bare metal surfaces.

Not suitable for direct application to powdery or friable surfaces whether previously painted or not.

Coats required

Apply three finishing coats to new surfaces to achieve a closed film.



SURFACE PREPARATION

NEW SURFACES

Textured Coatings

The textured coating must be allowed to dry for at least 18 hours – longer if the weather is wet and/or cold.

Brick and Stone Walls

Surfaces must be clean, dry and sound. Do not apply if, through age, the surface is powdery or friable.

Wallpaper

The surface must be clean, free from oil or soil marks. These can interfere with the adhesion of the coating.

PREVIOUSLY PAINTED SURFACES

Any loose or flaking paint/varnish must be completely removed.

Sound surfaces must be thoroughly sanded.

Do not apply to powdery or chalky surfaces (see Precautions).



HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Non-flammable.



ADDITIONAL INFORMATION

Packaging Size

5L

Storage Conditions

Store under cool dry conditions.

Disclaimers

For best colour and sheen consistency, it is advisable to use containers of the same batch number, or to mix different batches together in a large container, or to finish in a corner before starting a new container.

