

DULUX 30ML WET ROLLER COLOUR TESTER

TECHNICAL DATA SHEET

Version 1 – 2018 MARCH

THIS ISSUE SUPERSEDES ALL PREVIOUS PUBLICATIONS

PRODUCT DESCRIPTION

Dulux Wet Roller Tester provides a quick, easy and mess-free on-wall colour guide to select colour and eliminates uncertainty before tinting the bulk product of choice.

PRODUCT USES

- Excellent colour guide to test the colour before you paint the colour
- Quick and easy way to select colour and eliminates uncertainty.

FEATURES AND BENEFITS

- Quick, easy and mess-free, the built-in mini roller applies paint to the wall just like a decorating roller, so you can see exactly how your colour will look in your space before you order your paint.
- Unique Roller format gives better finish – smooth with no brush marks, more like the final finish
- Good for colour testing in projects
- Cost saving – colour is selected before bulk purchase

PRODUCT INFORMATION

Appearance	Mid-Sheen
Colour	Available in a range of ready to use wet-roller colour testers
Binder Type	Acrylic Polymer
Density at 23°C	Approx. 1.27
Solids Content	By weight: Approx. 47% By volume: Approx. 36%
Packaged Viscosity	Viscosity at 23°C: Approx. 100 KU
Spreading Rate	Approx. 0.25m ² per 30ml per coat depending on surface porosity, profile and application method.
Recommended DFT per coat	Min. 30µm. Max. 40µm.
Recommended WFT per coat	Min. 100µm. Max. 125µm
Flash Point	Non-flammable







APPLICATION INFORMATION

Mixing	Shake tester well before use.
Application Surface conditions	Surface Temperature between 10 - 35°C. Relative Humidity between 10 - 85 % OR 2°C above dew point minimum.

DULUX 30ML WET ROLLER COLOUR TESTER

APPLICATION INFORMATION

Application methods The bottle comes with an integrated easy to use mini roller, protected by a bottle cap

1	2	3	4	5	6
					
Shake the tester before using	Tear along the perforated line to open the bottle cap.	Remove the seal carefully. Close the bottle cap after use. Use within 6 hours from breaking the seal.	Hold the roller facing down while squeeze the tester gently to dispense a little bit of paint on the roller	Hold the tester from the side and apply vertically onto the wall	Repeat the application process to achieve the desired colour appearance allow the paint to dry for 2 hours in-between coats

Thinner	Thinning not recommended. Ready for use after thorough shaking.
Drying Time	Touch dry 1 hour at 23°C.
Recoating Time	2 hours at 23°C (Drying times will be extended during cold, wet or humid conditions). Replace bottle cap in-between coats to prevent the paint on the roller from drying.
Cleaning of equipment	For one-time use only. Clean any other equipment immediately with water.
Substrates	Suitable for previously painted water based paint in sound condition and appropriately prepared and primed new cement plaster, gypsum plaster, concrete, fibre cement, ceiling boards, composite boarding and wooden surfaces.
Precautions	Ensure that surfaces are sound and free from dust, oil, grease, dirt, and debris. Surfaces must be thoroughly dry - no more than 12% moisture content. Not suitable for touch ups. For one-time use only Do not apply during cold (below 10°C) or wet weather. Do not apply directly to substrate without priming. Not suitable for direct application to powdery or friable surfaces whether previously painted or not.
Coats Required	Apply two to three coats to achieve a continuous closed film and solid colour.

DULUX 30ML WET ROLLER COLOUR TESTER

HEALTH AND SAFETY INFORMATION

This product contains no added lead. Avoid contact with skin or eyes. Keep out of reach of children. If accidentally swallowed, seek medical advice immediately and show this container to the doctor. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible.

If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Do not empty into drains or watercourses. Ensure good ventilation during application and drying. It is recommended to use suitable protective clothing and equipment. To avoid the risk of spillage, always store and transport containers in a secure upright position. Refer to Material Safety Data Sheet for complete information.

ADDITIONAL INFORMATION

Packaging	30ml Ready to use wet roller testers
Storage Conditions	Store under cool dry conditions away from direct sunlight, heat and extreme cold.
Disclaimers	<p>Colour swatch references are as accurate as modern printing will allow. Please refer to the in-store stripe cards/standard card, for an accurate representation of the colour.</p> <p><i>The Wet Roller Colour Tester had a mid-sheen finish, and provides a guide to the selected colour. Among others, the following factors may affect final colour appearance of bulk product tinted using compared to the 30ml Wet Roller Colour Tester: product sheen and texture, colour and light reflections, application, surface texture and preparation.</i></p>

TDS STANDARD DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond Dulux control.

Important Note; Technology may change with time, necessitating changes to this Technical Data Sheet (TDS).

It is the responsibility of the user to ensure that the latest TDS is being used for reference. Dulux Technical Data Sheets are available on our website www.dulux.co.za or please contact: Dulux On-Line on 0860 330 111. Email ZA.Helpline@akzonobel.com

ICI Dulux (Pty) Ltd is part of AkzoNobel. ICI Dulux (Pty) Ltd Reg No.1946/020769/07