

## FAST PLASTER PRIMER MOISTURE TOLERANT



### PRODUCT USES

Recommended for use as a primer for new interior and exterior plastered walls.

Also suitable for coating surfaces such as brick, concrete and other masonry surfaces.



### FEATURES AND BENEFITS

Tolerates moisture of up to 30%, allowing early priming of newly plastered walls.

For interior and exterior use.

Can be over coated with decorative water based and solvent based topcoats.

Protects the topcoat from alkali attack.



### PRODUCT INFORMATION

<b>Colour</b>	White
<b>Density at 23°C</b>	Approx. : 1.27 kg/L
<b>Solids Content</b>	By weight : Approx. 52% By volume : Approx. 29%
<b>Packaged Viscosity</b>	Viscosity at 23°C : Approx 70 KU
<b>Spreading Rate</b>	Approx 7 to 8 m <sup>2</sup> per litre depending on surface porosity, profile and application method
<b>Recommended DFT per coat</b>	Min. 25µm. Max. 35µm.



### APPLICATION INFORMATION

<b>Application conditions</b>	Surface Temperature between 10 - 35°C Relative Humidity between 10 - 85 %
<b>Application methods</b>	Brush or roller Brush is preferred to work the material well into the surface.
<b>Thinner</b>	Thinning not recommended Ready for use after thorough stirring
<b>Drying Time</b>	Touch dry 2 hours (Drying times will be extended during cold, wet or humid conditions)
<b>Recoating Time</b>	18 hours
<b>Cleaning of equipment</b>	For clean up use <b>Fixit Brush Cleaner / Degreaser</b> or Mineral Turpentine
<b>Substrates</b>	Suitable for cement plaster, gypsum plaster, concrete, and other masonry surfaces

Designed for early priming of newly plastered walls





20L



5L



## APPLICATION INFORMATION

### PRECAUTIONS

All surfaces must be sound, clean and as dry as possible – no more than 30% moisture content.

Do not apply during cold (below 10°C) or wet weather.

Not suitable as a primer for metal surfaces.

Not suitable for direct application to powdery or friable surfaces whether previously painted or not.

Not designed to withstand natural weathering. It should be over coated within 48 hours.

### TOP COATING

Can be over coated with most Dulux decorative finishes. N.B. Whilst Dulux Trade Plaster Primer is tolerant to high levels of moisture, the topcoat in use may not be. Typical enamels and high quality water based products are only suited for walls with up to 12% moisture. Therefore, after application of Plaster Primer, please ensure that the topcoat is applied at the correct moisture level (Refer to relevant Technical Data sheets for more specific information. If further drying is required before topcoat application.)



## SURFACE PREPARATION

### NEW SURFACES

New plaster must be allowed to dry to at least 30% moisture before application.

Spot-prime metal strips and nail heads with appropriate metal primer.

### PREVIOUSLY PAINTED SURFACES

Strip loose and flaking paint completely.

Friable and porous surfaces must be removed and repaired.

Mould instructions. To kill lichen and algae growth, scrub with 1 of the following solutions: either 4:1 water/HTH (chlorine), or 4:1 water/JIK (sodium hypochlorite). Ensure that the areas are completely saturated, and allow the solution to react for a minimum of 4 hours. Rinse the complete wall surface thoroughly with clean water.

Chalked surfaces must be thoroughly brushed.

### FILLING

Fill all imperfections with the appropriate **Fixit Filler** and spot prime filled areas with **Dulux Trade Plaster Primer**.



## HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Flash Point 37°C.



## ADDITIONAL INFORMATION

### Storage Conditions

Store under cool dry conditions.