

## TRADE 65 MATT



### PRODUCT USES

Suitable for application to a variety of building surfaces which include new cement plaster, concrete, gypsum plaster and various types of composition boarding.



### FEATURES AND BENEFITS

- Good exterior durability
- High opacity - obliteration is normally achieved in one coat
- Easy to apply
- Good alkali resistance - can be used on new plaster
- Easy water clean-up



### PRODUCT INFORMATION

<b>Appearance</b>	Matt
<b>Colour</b>	White and the following tint bases: Pastel Base 7, Medium Base 8, and Dark Base 9 from the Dulux Colour System
<b>Density at 23°C</b>	Approx. : 1.54 kg/L
<b>Solids Content</b>	By weight : Approx. 56% By volume : Approx. 37%
<b>Packaged Viscosity</b>	Viscosity at 23°C : Approx 100 KU
<b>Spreading Rate</b>	Approx 8m <sup>2</sup> per litre depending on surface porosity, profile and application method
<b>Recommended DFT per coat</b>	Min. 25µm. Max. 35µm



### APPLICATION INFORMATION

<b>Application conditions</b>	Surface Temperature between 10 - 35°C Relative Humidity between 10 - 85 %
<b>Application methods</b>	Brush, roller or airless spray
<b>Thinner</b>	Thinning not recommended Ready for use after thorough stirring
<b>Drying Time</b>	Touch dry 30 minutes (Drying times will be extended during cold, wet or humid conditions)
<b>Recoating Time</b>	4 hours
<b>Cleaning of equipment</b>	Clean immediately with water

Good quality matt paint for interior and exterior walls and ceilings





20L



5L



1L



## APPLICATION INFORMATION

### Substrates

Suitable for cement plaster, gypsum plaster, concrete, fibre cement, and various types of composition boarding, as well as metal, PVC and wood provided appropriate preparation and priming is done.

### PRECAUTIONS

Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry - no more than 12% moisture content.

Do not apply during cold (below 10°C) or wet weather.

Do not apply directly to bare metal surfaces.

Not suitable for direct application to powdery or friable surfaces whether previously painted or not.

Essentially a wall coating. Areas subject to continual handling/soiling, e.g. cupboards and doorframes, use an **Eggshell Enamel**.

### COATS REQUIRED

Apply two to three finishing coats to new surfaces to achieve a closed film and solid colour.



## SURFACE PREPARATION

### NEW SURFACES

#### Cement Plaster (non friable)

It is recommended that fresh plaster should be allowed one week drying for every 5mm thickness; and longer in cold or damp weather.

Spot-prime metal strips and nail heads with appropriate metal primer.

Prime with one full coat **Dulux Trade Alkali Resistant Primer**.

#### Fibre Cement, Gypsum Plaster, Composition Boarding

Spot-prime metal strips and nail heads with appropriate metal primer.

Prime with one full coat **Dulux Trade Alkali Resistant Primer**.

#### Concrete

Remove any uncured cement, grease, and mould-release agents by high-pressure water blast, or wash with a strong solution of sugar soap. Rinse off thoroughly with clean water.

Prime with one full coat **Dulux Trade Alkali Resistant Primer**.

### PREVIOUSLY PAINTED SURFACES

#### Sound, not powdery

Clean surfaces with **Fixit Sugar Soap**. Wash down with water.

For emulsion surfaces apply finishing coats.

For enamel surfaces, sand to a matt finish to aid adhesion and follow with a coat of **Dulux Undercoat for All Surfaces**. Apply finishing coats.

#### Old Paint in poor condition

Strip loose and flaking paint completely and spot prime bare areas with **Dulux Trade Alkali Resistant Primer**.

Friable and porous surfaces must be removed and repaired.

Mould instructions. To kill lichen and algae growth, scrub with one of the following solutions: either 4:1 water/HTH (chlorine), or 4:1 water/JIK (sodium hypochlorite). Ensure that the areas are completely saturated, and allow the solution to react for a minimum of 4 hours. Rinse the complete wall surface thoroughly with clean water.

#### Filling

Fill all imperfections with the appropriate **Fixit Filler** and spot prime filled areas with **Dulux Primer for new Plaster** once the crack filler has dried properly. Failure to do this will result in uneven sheen levels between the repaired and normal areas.



## HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Non-flammable.



## ADDITIONAL INFORMATION

### Storage Conditions

Store under cool dry conditions.