

FILLER COAT



PRODUCT USES

Gives a perfect finish to newly plastered walls and ceiling boards.



FEATURES AND BENEFITS

For interior and exterior use.

Fills and smoothes out minor plaster defects.

Improves the appearance of premium topcoats by creating a smooth base of even porosity.

Quick drying - topcoats can be applied during the same day.

Low odour - can be used in odour sensitive areas.

Easy to apply by brush and roller.



PRODUCT INFORMATION

Colour	White
Density at 23°C	Approx. : 1.37 kg/L
Solids Content	By weight : Approx. 48% By volume : Approx. 29%
Packaged Viscosity	Viscosity at 23°C : Approx 100 KU
Spreading Rate	Approx 6 to 8m ² per litre depending on surface porosity, profile and application method
Recommended DFT per coat	Min. 25µm. Max. 35µm.



APPLICATION INFORMATION

Application conditions	Surface Temperature between 10 - 35°C Relative Humidity between 10 - 85 %
Application methods	Brush, roller or airless spray
Thinner	Thinning not recommended Ready for use after thorough stirring
Drying Time	Touch dry 30 minutes (Drying times will be extended during cold, wet or humid conditions)
Recoating Time	4 hours
Cleaning of equipment	Clean immediately with water
Substrates	Suitable for cement plaster, gypsum plaster, concrete, fibre cement, ceiling boards and all types of composition boarding.

Top quality acrylic filler coat for interior and exterior use





20L



5L



APPLICATION INFORMATION

Precautions

Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry - no more than 12% moisture content.

Do not apply during cold (below 10°C) or wet weather.

Do not apply directly to bare metal surfaces.

Not suitable for direct application to powdery or friable surfaces whether previously painted or not.

Coats Required

Apply one or two coats depending on the degree of filling required.



SURFACE PREPARATION

NEW SURFACES

Cement Plaster (non friable), Gypsum Plaster, Composition Boarding, Fibre Cement

It is recommended that fresh plaster should be allowed 1 week drying for every 5mm thickness; and longer in cold or damp weather.

Spot-prime metal strips and nail heads with appropriate metal primer.

Prime with **Dulux Trade Alkali Resistant Plaster Primer**.

Concrete

Remove any uncured cement, grease, and mould-release agents by high-pressure water blast, or wash with a strong solution of sugar soap. Rinse off thoroughly with clean water.

Prime with **Dulux Trade Alkali Resistant Plaster Primer**.

Filling

Fill all imperfections with the appropriate **Fixit Filler** and spot prime filled areas with **Dulux Trade Alkali Resistant Plaster Primer** before applying **Fillercoat**.



HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Non-flammable.



ADDITIONAL INFORMATION

Storage Conditions

Store under cool dry conditions.