

## SUPERGRIP



### PRODUCT USES

Suitable for use as a primer on:

- PVC gutters and down pipes
- Previously painted enamel surfaces
- Wood
- Ceramic tiles
- New concrete
- Melamine/Formica®
- Glass
- Galvanised metal



### FEATURES AND BENEFITS

Compatible with Dulux decorative finishes.

Extreme Adhesion – from walls to ceramic tiles.

Quick drying and Low Odour – rapid room re-entry.

Suitable for interior and exterior use.



### PRODUCT INFORMATION

<b>Colour</b>	White
<b>Density at 23°C</b>	Approx. : 1.27 kg/L
<b>Solids Content</b>	By weight : Approx. 49% By volume : Approx. 37%
<b>Packaged Viscosity</b>	Viscosity at 23°C : Approx 95 KU
<b>Spreading Rate</b>	Approx 10m <sup>2</sup> per litre depending on surface porosity, profile and application method
<b>Recommended DFT per coat</b>	Min. 25µm. Max. 35µm.



### APPLICATION INFORMATION

<b>Application conditions</b>	Surface Temperature between 10 - 35°C Relative Humidity between 10 - 85 %
<b>Application methods</b>	Brush, roller or spray application
<b>Thinner</b>	Thinning not recommended Ready for use after thorough stirring
<b>Drying Time</b>	Touch dry 2 hours (Drying times will be extended during cold, wet or humid conditions)
<b>Recoating Time</b>	12 hours minimum Allow 48 hours drying time for solvent-based topcoats
<b>Cleaning of equipment</b>	Clean immediately with water
<b>Substrates</b>	Suitable for PVC gutters and down pipes, previously painted enamel surfaces, wood, ceramic tiles, new concrete, Melamine/Formica®, glass, galvanised metal.

Versatile  
multi-surface  
waterborne  
primer





## APPLICATION INFORMATION

### Precautions

Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry - no more than 12% moisture content.

Do not apply during cold (below 10°C) or wet weather.

Do not apply directly to bare metal surfaces.

Not suitable for direct application to powdery or friable surfaces whether previously painted or not.

Not designed to withstand natural weathering. It should be over coated within 48 hours particularly in a marine atmosphere.

### Top Coating

Can be over coated with most Dulux decorative finishes.



## SURFACE PREPARATION

### NEW SURFACES

#### Wooden surfaces (doors, frames, furniture, toys)

Sand smooth. Remove all splintered and discoloured wood and apply one coat direct.

#### Ceramic tiles

Ensure surfaces are clean, dry and dust free. Tiles around kitchen sinks and bath/shower areas must be degreased with either **Fixit Brush Cleaner/Degreaser** or a water-miscible household degreaser followed by thorough rinsing with water. All loose grout must also be repaired prior to painting. N.B. Not suitable for floor tiles.

#### Melamine/Formica®

Dust and degrease. Areas that have developed a sheen due to repeated handling will have to be sanded. Apply one coat direct. N.B: Only suitable for areas that receive limited wear and tear e.g. Kitchen, bathroom and bedroom cupboard doors and frame work.

#### Galvanised Iron

Clean and degrease with **Dulux Galvanised Iron Cleaner**. A water-break free surface indicates thorough cleaning - running water should not form droplets.

Areas with red rust must be wire brushed and primed with **Dulux Galvanised Iron Primer**.

#### Glass

Clean to remove dust and grease. Apply one coat direct.

### PVC

Lightly sand surfaces to improve adhesion. Clean and degrease with either **Fixit Brush Cleaner/Degreaser** or water-miscible household degreaser.

Rinse thoroughly with water and allow drying. Apply one coat direct.

### Brick and Plaster

Remove all dust and loose grit. Ensure surfaces are completely dry. It is recommended that fresh plaster should be allowed one week drying for every 5mm thickness; and longer in cold or damp weather.

### PREVIOUSLY PAINTED SURFACES

Previously painted Enamels, Varnishes and Polyurethane finishes

Remove all loose and flaking paint.

Sandpaper well with wet-and-dry paper to remove surface gloss.

Clean away all contaminants with water-miscible household degreaser, rinse thoroughly with clean water, and allow drying.

Apply one coat direct.

### FILLING

Fill all imperfections with the appropriate **Fixit** filler before using primer.



## HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Non-flammable.



## ADDITIONAL INFORMATION

### Storage Conditions

Store under cool dry conditions.