

QUICK DRY VARNISH

Dulux Trade Quick Dry Varnish is a water-based interior varnish containing polyurethane which gives a tough and durable finish. It can be used over bare wood and previously stained or varnished surfaces. Rapid drying properties allow work to be completed quickly.

KEY BENEFITS

- Recoatable in 2 Hours
- Doors, Trim, Furniture and Joinery
- Water-Based

PRODUCT INFORMATION

Typical Use

Suitable for use on interior wood, veneer, cork and chipboard.

Pack Size

1L and 2.5L.

Colour Range

Clear Gloss or Satin and colours (in Satin only – see appropriate **Dulux Trade** colour literature or visit duluxtrade.co.uk).

Composition (nominal)

Pigment: Inert Matting Agents.

Binder: Acrylic Copolymer Emulsion plus Polyurethane Dispersion.

Solvent: Water.

Volume Solids

28% (nominal).

SURFACE PREPARATION

To get the best results, ensure surfaces to be varnished are sound, clean and dry (new surfaces particularly must be fully dry) before treating. Clean off any wax polish, grease or finger marks with white spirit.

Remove any defective or poorly adhering varnish. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

When applying to previously stained or varnished surfaces, rub down thoroughly along the grain of the wood to provide a 'key'. Use 'wet flattening'

methods where possible, then wipe off with a damp, lint free cloth.

New or bare surfaces must also be rubbed down with a suitable grade of abrasive paper and dusted off (refer to your COSHH Assessment).

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE AND DURING USE. Apply 2 or 3 coats of Dulux Trade Quick Dry Varnish. For best results lightly sand down with a fine grade abrasive paper, along the grain of the wood between coats of varnish. Then wipe off with a damp, lint free cloth. Avoid the inhalation of dust and wear a suitable face mask if dry sanding.

Dulux Trade Quick Dry Varnish can be used over previously stained wood to vary sheen level i.e. gloss/satin. Use direct from the can.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

APPLICATION METHOD

Brush or roller only. Do not spray. For best results, use a good quality synthetic (nylon polyester) brush, designed for use with water-based paints, stains and varnishes. Brush out evenly, taking care to avoid overlaps and finish along the grain.

As with all water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

Practical Coverage

On smooth surfaces of average porosity, a guide to the practical coverage is up to 20m² per litre.

Thinning

Do not thin this product.

Spray Recommendations

This product is not suitable for spray application.



QUICK DRY VARNISH

Drying Times

Single coat at standard thickness:

Touch Dry: 30 minutes.

Recoat: 2 hours.

Cleaning Up

After use, remove as much product as possible from brushes before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/pp.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/e): 130g/l (2010). This product contains max. 10g/l VOC. VOC content: Low (0.30-7.99%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:0333 222 70 70).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 604) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at duluxtrade.co.uk/pp