



PROTECTIVE WOODSHEEN WOODSTAIN

Dulux Trade Protective Woodsheen Woodstain is a solvent-based, medium build satin finish for interior wood. Specially formulated to colour and protect interior wood, providing a durable finish to resist wear-and-tear.

KEY BENEFITS

- 4 Year Protection
- Doors, Trim, Furniture and Joinery
- Solvent-Based

PRODUCT INFORMATION

Typical Use

Suitable for interior hardwoods and softwoods.

Pack Size

1L, 2.5 and 5L.

Colour Range

See appropriate **Dulux Trade** colour literature or visit duluxtrade.co.uk.

Composition (nominal)

Pigment: Special Transparent Iron Oxide Micro Pigments and Organic Pigments.

Binder: Oil modified alkyd.

Solvent: Low Odour aliphatic hydrocarbons.

Volume Solids

White: 48% (nominal). Colours will vary.

SURFACE PREPARATION

To get the best results, ensure surfaces to be varnished are sound, clean and dry (new surfaces particularly must be fully dry) before treating. Remove all paint, varnish and defective coatings. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Remove defective glazing material, clean the rebates and any loose or open joints. Replace any rotten wood and troublesome knots with preservative-treated timber.

Remove and treat any mould, algae, lichen or moss with **Weathershield** Multi-Surface Fungicidal Wash*.

Rub down thoroughly along the grain of the wood to remove sharp edges and any grey weathered wood. Remove dust with a damp lint free cloth.

Fill any surface defects, open joints etc. and replace any missing glazing material. Do not use linseed oil putty for glazing (or making good) with natural wood finishes, use external beads set in an appropriate non-setting mastic or a special glazing compound.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Do not thin. After suitable preparation, apply 2 coats of **Dulux Trade** Protective Woodsheen Woodstain.

Do not use on resinous wood or woodwork with a history of blistering. The maximum benefits of this system will only be realised when used as directed above on good quality timber that conforms BS EN 942: 1996 (or as amended), in conjunction with good component design.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

APPLICATION METHOD

Brush only. For Health and Safety reasons relating to all solvent-based paints, spray application is not recommended.

As with all solvent-based paints, do not apply at temperatures below 5°C (as recommended by British Standard BS 6150).

Practical Coverage

On smooth surfaces of average porosity, a guide to the practical coverage is up to 20m² per litre.

Thinning

Do not thin this product.

Spray Recommendations

This product should not be sprayed.



PROTECTIVE WOODSHEEN WOODSTAIN

605

Drying Times

Single coat at standard thickness:

Touch Dry: 4-6 hours.

Recoat: 16-24 hours.

Cleaning Up

After use, remove as much product as possible from brushes before cleaning with brush cleaner.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/pp.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/e): 400g/l (2010). This product contains max. 399g/l VOC. VOC content: High (25-50%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

***Weathershield** Multi-Surface Fungicidal Wash contains: Benzalkonium Chloride.

Use biocides safely. Always read the label and product information before use.

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 605) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at duluxtrade.co.uk/pp

AkzoNobel